

# 96PR-100-UB3-M

**203 dpi Mobile Printer, 3.14", 4 ips,  
USB/Bluetooth**



## Features

- Easy handling of paper cut by pushing a button with one hand
- Supports various drivers and SDK: Windows, Win CE, Linux, iOS, and Android
- IP54 certificate, strong and powerful design against dust and water
- Lithium- ion rechargeable battery : 130M(about 1300 pieces) printable

## Specifications

<b>Printing</b>	Method	Direct Thermal
	Speed	Max. 100 mm (3.94 in.)/ sec.
<b>Resolution</b>		203 dpi
<b>Paper</b>	Paper Type	Thermal Receipt
	Width	Max. 80 mm (3.14 in.)
	Thickness	0.06 ~ 0.09 mm (0.002 ~ 0.003 in.)
	External Diameter	Max. Ø50 mm (1.96 in.)
	Internal Diameter	12.5 mm (0.49 in.)
<b>Character</b>		Font A (12x24), Font B(9x17), Asian, Font(KOR,JPN,CHN-GB2312,CHN-Big5), Font0/1/2/4/5/6/7, Resident TTF, Downloadable TTF, FontA-H, FontGS, Resident TTF(Font0), Font 1-8
<b>Barcode</b>	1D	EAN-8,EAN8(+2+5), EAN-13, EAN13(+2+5), Codabar, Code11, Code39, Code93, Code128, ITF, LUPCA(+2+5), UPC-E, UPC-E(+2+5), Planet, UPC-A etc
	2D	PDF417, QR, Maxicode, RSS14, TLC39, Datamatrix, Aztec, MicroPDF417
<b>Emulation</b>		ESC/POS, CPCL, ZPL Command compatible
<b>Driver</b>		Windows Driver(10, 2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Window CE & Mobile Driver & SDK (CE 4.2-, Mobile 5.0-), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1-) SDK, Blackberry SDK, Symbian
<b>Sensor</b>		Black mark, Cover open, Paper end
<b>Reliability</b>	TPH	50 km (31 mile)
	Pulse Activation	50,000,000 pulse or more (12.5% Print Ratio)
<b>Interface</b>	Standard	USB
	Option	Wi-Fi (802.11a/b/g/n) or Bluetooth Smart Ready(Bluetooth 4.2+BLE)
<b>Battery Charger</b>	Input	AC100-240V, 50/60Hz
	Output	8.4V , 800-1400mA
<b>Battery</b>	Battery Type	Li-ion
	Output	7.4V, 2000mAh
	Charging Time	3Hrs (77Hrs stand-by)
<b>Cutter</b>		AMC(Advanced Manual Cutter)
<b>Dimension (W x D x H)</b>		107.5 x 145 x 56 mm (4.23 x 5.7 x 2.2 in.)
<b>IP</b>		IP54
<b>Weight</b>		415.3 g (0.91 lb.) with Battery
<b>Temperature</b>	Operation	-10 ~ 50°C (14 ~ 122°F)
	Storage	-20 ~ 60°C (-4 ~ 140°F)
<b>Humidity</b>	Operation	10 ~ 80%
	Storage	10 ~ 90%

## Ordering Information

Part Number	Description
96PR-100-UB3-M	Mobile Printer, 203dpi, 4 ips, USB/Serial, US power cord