

96PR-300-UE-SB

180 dpi POS Printer, 2.83", 12 ips,
USB/Ethernet



Features

- Energy Star qualified for power efficiency
- High speed printing : 300mm/sec
- ESC/POS command compatible
- Auto cutter
- Supports various drivers and SDK: Windows, Win CE, Linux, iOS, and Android
- Supports wall mount installation

Specifications

Printing	Method	Direct Thermal
	Speed	Max. 300 mm (11.8 in.) /sec
	Width	72 mm (2.83 in.) 512 dots/line
	Resolution	180 dpi
Paper	Type	Thermal Paper
	Width	50 ~ 82.5 mm (1.97 ~ 3.25 in.)
	Thickness	0.06 ~ 0.09 mm (0.002 ~ 0.003 in.)
	Roll Diameter	Max. Ø80.0 mm (3.15 in.)
	Roll Core Inner	12.5 ± 0.5 mm (0.49 ± 0.02 in.)
Reliability	TPH Life	160 km (99.41 mile)
	MCBF	6,000,000 lines
Auto Cutter		1,500,000 Cuts (Guillotine)
Emulation		ESC/POS Command compatible
Driver		Windows Driver(2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Windows CE & Mobile Driver & SDK(CE 4.2 ~, Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1 ~) SDK, Windows SDK
Sensor	Standard	Paper end, Paper Low, Cover Open
	Option	Black Mark
Interface		USB (B Type), Ethernet
Power Supply	Type	External SMPS
	AC	100 ~ 240 V _{AC} 50/60 Hz
	DC	24 V _{DC} / 1.75A
Dimension (W x D x H)		152 x 204 x 150 mm (5.98 x 8.03 x 5.9 in.)
Weight		1.7 kg (3.74 lb.)
Temperature	Operation	0 ~ 45°C (32 ~ 113°F)
	Storage	-20 ~ 60°C (-4 ~ 140°F)

Ordering Information

Part Number	Description
96PR-300-UE-SB	Desktop Direct Thermal Receipt Printer, 180 dpi, USB/Ethernet, US power cord
96PR-300-UE-SBA	Desktop Direct Thermal Receipt Printer, 180 dpi, USB/Ethernet, AU power cord
96PR-300-UE-SBE	Desktop Direct Thermal Receipt Printer, 180 dpi, USB/Ethernet, EU power cord

Packing List

- Adapter
- AC cord (1.5m)
- CD (manual, drivers, utility, etc.)
- RS-232 cable (9-pin + 25-pin, 1.8m)
- Roll paper