

# EKI-7708G-4FP EKI-7708G-4FPI

## 4GE+4G SFP Port Gigabit Managed Redundant Industrial PoE Switch



### Features

- 4 x IEEE 802.3 af/at PoE Gigabit ports + 4 SFP ports
- SFP socket for Easy and Flexible Fiber Expansion
- Redundancy: X-Ring Pro (ultra high-speed recovery time < 20 ms), RSTP/STP (802.1w/1D)
- IXM function enables fast deployment
- Security: 802.1x (Port-Based, MD5/TLS/TTLS/PEAP Encryption), RADIUS
- Management: SNMP v1/v2c/v3, WEB, Telnet, Standard MIB, Private MIB
- NEMA TS2 for Traffic Control
- EN50121-4 approval for Railway trackside deployment
- -40 ~ 75°C wide-range operating temperature (EKI-7708G-4FPI)
- Dual 48 V<sub>DC</sub> power input and 1 relay output

### Introduction

EKI-7708G-4FP/4FPI supports 4 Gigabit IEEE 802.3 af/at PoE ports and 4 SFP (mini-GBIC) ports. They can provide up to 30 watts per port to fulfill high power consumption PD (Power Device) requirements. They are embedded with Advantech's IXM function, which can benefit users for fast deployment and can dramatically save engineers time and cost. The EKI-7708G series also supports NMS to help IT managers with networking maintenance and failure prevention. Finally, the EKI-7708G series is equipped with X-Ring Pro which can achieve ultra high speed recovery time of less than 20 ms to ensure network stability. The switch also features a wide -40° to 75°C operating temperature (EKI-7708G-4FPI) and NEMA TS2 rating, making the switch an ideal solution for use in traffic applications. EKI-7708G-4FP/4FPI has successfully passed the EN50121-4 European railway standard requirements for emissions and railway platform and trackside deployment.

### Specifications

#### Interface

- **I/O Port** 4 x 10/100/1000Base-T/TX RJ-45  
4 x SFP (mini-GBIC) port
- **Console port** RS-232 (RJ45)
- **Power Connector** 6-pin screw Terminal Block (including relay)

#### Physical

- **Enclosure** Metal Shell
- **Protection Class** IP 30
- **Installation** DIN-Rail
- **Dimensions (W x H x D)** 74 x 152 x 105 mm (2.91" x 5.98" x 4.13")

#### LED Display

- **System LED** PWR1, PWR2, SYS, Alarm and R.M.
- **Port LED** Link / Speed / Activity

#### Environment

- **Operating Temperature** -40 ~ 75°C (-40 ~ 167°F) (7708G-4FPI)  
-10 ~ 60°C (-40 ~ 140°F) (7708G-4FP)
- **Storage Temperature** -40 ~ 85°C
- **Ambient Relative Humidity** 10 ~ 95% (non-condensing)
- **Humidity** 10 ~ 95% (non-condensing)

#### Power

- **Power Consumption** 12.1W @ 48V<sub>DC</sub> (System)
- **Power Input** 48 V<sub>DC</sub> (46 to 57 V<sub>DC</sub>),  
53 ~57 V<sub>DC</sub> is recommended for 802.3at,  
redundant dual power input
- **Power Budget** 120W
- **Fault Output** 1 Relay Output

#### Certification


- **EMI** CE, FCC Class A
- **EMC** EN 61000-4-2  
EN 61000-4-3  
EN 61000-4-4  
EN 61000-4-5  
EN 61000-4-6  
EN 61000-4-8  
EN50121-4
- **Shock** IEC 60068-2-27
- **Freefall** IEC 60068-2-32
- **Vibration** IEC 60068-2-6
- **Security** IEC 62443-4-2 SL2
- **Traffic control** NEMA TS2
- \*= Compliant
- **Patent** <http://www.advantech.com/legal/patent>

#### L2 Features

- **L2 MAC Address** 8K
- **Jumbo Frame** 9216 Bytes
- **VLAN Group** 256 (VLAN ID 1 ~ 4094)
- **VLAN Arrange** Port based VLAN, Q-in-Q (VLAN Stacking), GVRP
- **Port Mirroring** Per port, Multi-source port,
- **IP Multicast** IGMP Snooping v1/v2/v3, MLD Snooping, IGMP Immediate leave
- **Storm Control** Broadcast, Multicast, Unknown unicast
- **Redundancy** IEEE 802.1D-STP, IEEE 802.1s-MSTP, IEEE 802.1w-RSTP, X-Ring Pro, with ultra high-speed recovery time less than 20ms

## Dimensions

Unit: mm [inch]



**Panel Cut-out Dimensions: 105 x 152 x 74 (4.134" x 5.98" x 2.913")**

### QoS

- **Priority Queue Scheduling** WRR (Weighted Round Robin), SP (Strict Scheduling Priority) Hybrid Priority
- **Class of Service** IEEE 802.1p Based CoS, IP TOS, DSCP based CoS
- **Rate Limiting** Ingress Rate Limit, Egress Rate Limit
- **Link Aggregation** IEEE 802.3ad Dynamic Port Trunking, Static Port Trunking

### Security

- **Port Security** Static, Dynamic
- **Authentication** 802.1x (Port-Based, MD5/TLS/TTLS/PEAP Encryption)

### Management

- **DHCP** Client, Server, Option66/67/82
- **Access** SNMP v1/v2c/v3, WEB, Telnet, RMON, Standard MIB, Private MIB
- **Security access** SSH2.0, SSL
- **Software upgrade** TFTP, HTTP, Dual Image
- **NTP** SNTP client

### Ordering Information

- **EKI-7708G-4FPI-BE** 4GE + 4G SFP Port Managed PoE Ethernet Switch / Wide Temp
- **EKI-7708G-4FP-BE** 4GE + 4G SFP Port Managed PoE Ethernet Switch