



SQF-C8B 720-D

PCIe Gen.3 x2 M.2 2280 SSD



Features

- NGFF M.2 2280 (B+M Key)
- Compliant with NVMe 1.3
- AES-256 Support & TCG-OPAL Compliant
- Supports LDPC & RAID ECC
- Support H/W Write Protection
- GUI management tool & software API package
- Multiple Temperature Range Product Selection



Specifications

Connect Type	NGFF B+M Key
Flash type	3D TLC
Capacity	128GB ~ 2TB
Transfer Mode	PCIe Gen.3 x2
Max. Power Consumption	Read: 2.9 W, Write: 2.9 W
Sustained R/W Performance (*)	up to 1,750/ 1,650 MB/sec
Operating Temperature	Commercial Temperature: 0 to +70 °C Minus Temperature: -20 to +85 °C Extended Temperature: -40 to +85 °C
Shock Resistance	1,500 G, peak / 0.5 ms
Vibration Resistance	20 G, peak / 80 ~ 2000 Hz
Dimensions (mm)	80.0 x 22.0 x 3.8

(*) These values are for reference only; they may change according to the flash memory used.

Ordering Information

PN	Description
SQF-C8BV2-128GDEDC	SQF PCIe/NVMe M.2 2280 OPAL 720-D 128G 3D TLC BiCS5 (0~70°C)
SQF-C8BV2-256GDEDC	SQF PCIe/NVMe M.2 2280 OPAL 720-D 256G 3D TLC BiCS5 (0~70°C)
SQF-C8BV2-512GDEDC	SQF PCIe/NVMe M.2 2280 OPAL 720-D 512G 3D TLC BiCS5 (0~70°C)
SQF-C8BV4-1TDEDC	SQF PCIe/NVMe M.2 2280 OPAL 720-D 1T 3D TLC BiCS5 (0~70°C)
SQF-C8BV4-2TDEDC	SQF PCIe/NVMe M.2 2280 OPAL 720-D 2T 3D TLC BiCS5 (0~70°C)
SQF-C8BV2-128GDEDM	SQF PCIe/NVMe M.2 2280 OPAL 720-D 128G 3D TLC BiCS5 (-20~85°C)
SQF-C8BV2-256GDEDM	SQF PCIe/NVMe M.2 2280 OPAL 720-D 256G 3D TLC BiCS5 (-20~85°C)
SQF-C8BV2-512GDEDM	SQF PCIe/NVMe M.2 2280 OPAL 720-D 512G 3D TLC BiCS5 (-20~85°C)
SQF-C8BV4-1TDEDM	SQF PCIe/NVMe M.2 2280 OPAL 720-D 1T 3D TLC BiCS5 (-20~85°C)
SQF-C8BV4-2TDEDM	SQF PCIe/NVMe M.2 2280 OPAL 720-D 2T 3D TLC BiCS5 (-20~85°C)
SQF-C8BV2-128GDEDE	SQF PCIe/NVMe M.2 2280 OPAL 720-D 128G 3D TLC BiCS5 (-40~85°C)
SQF-C8BV2-256GDEDE	SQF PCIe/NVMe M.2 2280 OPAL 720-D 256G 3D TLC BiCS5 (-40~85°C)
SQF-C8BV2-512GDEDE	SQF PCIe/NVMe M.2 2280 OPAL 720-D 512G 3D TLC BiCS5 (-40~85°C)
SQF-C8BV4-1TDEDE	SQF PCIe/NVMe M.2 2280 OPAL 720-D 1T 3D TLC BiCS5 (-40~85°C)
SQF-C8BV4-2TDEDE	SQF PCIe/NVMe M.2 2280 OPAL 720-D 2T 3D TLC BiCS5 (-40~85°C)
SQF-C8BZ2-32GDEDC	SQF PCIe/NVMe M.2 2280 OPAL 720-D 32G 3D sTLC BiCS5 (0~70°C)
SQF-C8BZ2-64GDEDC	SQF PCIe/NVMe M.2 2280 OPAL 720-D 64G 3D sTLC BiCS5 (0~70°C)
SQF-C8BZ2-128GDEDC	SQF PCIe/NVMe M.2 2280 OPAL 720-D 128G 3D sTLC BiCS5 (0~70°C)
SQF-C8BZ4-256GDEDC	SQF PCIe/NVMe M.2 2280 OPAL 720-D 256G 3D sTLC BiCS5 (0~70°C)
SQF-C8BZ4-512GDEDC	SQF PCIe/NVMe M.2 2280 OPAL 720-D 512G 3D sTLC BiCS5 (0~70°C)
SQF-C8BZ2-32GDEDE	SQF PCIe/NVMe M.2 2280 OPAL 720-D 32G 3D sTLC BiCS5 (-40~85°C)
SQF-C8BZ2-64GDEDE	SQF PCIe/NVMe M.2 2280 OPAL 720-D 64G 3D sTLC BiCS5 (-40~85°C)
SQF-C8BZ2-128GDEDE	SQF PCIe/NVMe M.2 2280 OPAL 720-D 128G 3D sTLC BiCS5 (-40~85°C)
SQF-C8BZ4-256GDEDE	SQF PCIe/NVMe M.2 2280 OPAL 720-D 256G 3D sTLC BiCS5 (-40~85°C)
SQF-C8BZ4-512GDEDE	SQF PCIe/NVMe M.2 2280 OPAL 720-D 512G 3D sTLC BiCS5 (-40~85°C)